

**Amendments to the Claims:**

The following listing of claims will replace all prior versions, and listings, of claims in the application:

1. (Currently Amended) A projector ~~including having~~ a light source, a light modulating device that ~~modulate,modulates light in accordance with image information,~~ beams emitted from the light source in accordance with image information to form an optical image, and a case that accommodates the light source and the light modulating devices, and the projector enlarges and projects the optical image formed by the light modulating devices, the projector ~~including~~comprising:

~~a leg portion~~leg portions that are disposed so as to be extendable from and retractable to an outer peripheral surface of the case to adjust ~~the a~~ projection position of the enlarged and projected optical ~~image,~~image;

an intake opening that is formed in ~~the a~~ surface of the case disposed with the ~~leg portions,~~portions; and

an intake fan that is disposed inside the case near the intake opening and that introduces cooling air from ~~the outside~~ of the case,

~~wherein~~ an intake surface of the intake fan is being disposed at an inclination with respect to ~~the a~~ plane of the case in which the intake opening is formed.

2. (Currently Amended) The projector according to claim 1, further ~~including~~ including:

a power supply circuit ~~for supplying~~that supplies power to the light source and the light modulating ~~devices,~~devices; and

~~and~~ a light source drive circuit ~~for driving~~that drives the light ~~source,~~source;

~~wherein~~ the intake fan is being used in a cooling flow path that cools ~~the a~~ power supply circuit and the light source drive circuit.

3. (Currently Amended) The projector according to claim 2, ~~wherein the~~ cooling flow path of cooling air introduced by the intake fan ~~is-being~~ set independent from another cooling flow path.

4. (Currently Amended) The projector according to claim 3, ~~wherein the~~ cooling flow path ~~is-being~~ configured to allow the cooling air to circulate along the surface of the case in which the intake opening is formed.

5. (Currently Amended) The projector according to ~~one of claim 3 or 4~~ claim 3, ~~wherein the~~ cooling flow path ~~is-being~~ partitioned by tabular bodies disposed vertically from an inner surface of the case.

6. (Currently Amended) The projector according to ~~any of claims 2 through 5~~ claim 2, ~~wherein the~~ power supply circuit and the light source drive circuit ~~are-being~~ surrounded by cylindrical air-guiding bodies and the cooling air from the intake fan ~~is-being~~ supplied to ~~the~~ an inside of each air-guiding body.

7. (Currently Amended) The projector according to claim 6, ~~wherein the~~ intake fan ~~is-being~~ attached to the air-guiding bodies.

8. (Currently Amended) The projector according to claim 1, ~~wherein~~  
the intake opening ~~is-being~~ a first intake opening,  
the intake fan ~~is-being~~ a first intake fan,  
a discharge opening through which air inside the case is discharged to ~~the~~ a  
outside of the case ~~is-being~~ disposed in a side of the case, and  
the projector further ~~includes~~ including:  
a second intake opening that is disposed in the case separately from the first  
intake ~~opening,~~ opening;  
a second intake fan that is disposed near the second intake opening and  
introduces cooling air from the outside of the ~~ease,~~ case;

a first cooling system that uses the second intake fan to introduce, through the second intake opening to ~~the~~an inside of the case, air from ~~the~~an outside of the case, circulates the air to the discharge opening so that the air is discharged through the discharge opening to the outside of the case, to thereby cool the light modulating devices and the light ~~source,source;~~ and

a second cooling system that uses the first intake fan to introduce, through the first intake opening to the inside of the case, air from the outside of the case, circulates the air to the discharge opening so that the air is discharged through the discharge opening to the outside of the case, to thereby cool the power supply circuit and the light source drive circuit.

9. (Currently Amended) The projector according to claim 8, ~~wherein~~ the first cooling air flow and the second cooling air flow ~~are~~being discharged through different regions in the discharge opening.

10. (Currently Amended) The projector according to ~~one of claim 8 or 9~~claim 8, ~~wherein~~

the power supply circuit ~~is~~being disposed inside a cylindrical first air-guiding body,

the light source drive circuit ~~is~~being disposed inside a cylindrical second air-guiding body,

part of the second cooling air flow ~~is~~being introduced to the inside of the first air-guiding body and another part of the second cooling air flow ~~is~~being introduced to the inside of the second air-guiding ~~body,body;~~ and

the air flow circulating through the first air-guiding body and the air flow circulating through the second air-guiding body ~~are~~being discharged through different regions in the discharge opening.

11. (Currently Amended) The projector according to ~~any of claims 8 through 10~~claim 8, wherein an intake surface of the first intake fan is ~~is~~being disposed at an inclination so as to be distanced from the first intake opening as it approaches the discharge opening.